

LW / IW / GPW Series In-Wall



LW-6




IWP-6





GPW-6


The LW, IW and GPW series speakers are quality-built, in-wall speakers. Designed and built to provide fine audio at the most competitive pricing on the face of the earth. The IW Series carries the same life-time warranty by which all TruAudio speakers are known.


The Ghost series in-wall is the latest speaker that incorporates our original US patent to give this speaker its super flush, almost frameless appearance. These speakers also include our new ground-breaking Wave Guide technology, to give the tweeter a fuller dispersion pattern. Each speaker comes with two Wave Guide Tweeters, one straight for standard installations, and a second one that has a 22° angle for off-center installations. The Ghost Series in-wall speaker pushes the concept of aesthetics and incredible performance. A specially designed speaker housing hides the entire frame once the grill is installed. With this new design, the speaker blends seamlessly into the room's environment and is a labor saver.

speaker Type:	LW-6 In-wall, 2 way
Woofers:	6.5" polypropylene
Tweeters:	.75" Mylar
Power:	5 - 60 watts
Impedance:	8 ohms
Freq Response:	55 - 20k Hz
Sensitivity:	88 dB
Grill Type:	Micromesh, aluminum
Finish Dims:	12" (304mm) H, 8.63" (219mm) W, 3" (76mm) D
Cutout Dims:	11" (279mm) H, 7.5" (191mm) W
Family:	 ARCHES

speaker Type:	IWP-6 In-wall, 2 way
Woofers:	6.5" Injected polypropylene
Tweeters:	1" silk soft dome, swivel
Power:	5 - 100 watts
Impedance:	8 ohms
Freq Response:	55 - 20k Hz
Sensitivity:	90 dB
Grill Type:	Micromesh, aluminum
Finish Dims:	12.13" (308mm) H, 8.75" (222mm) W, 3" (76mm) D
Cutout Dims:	10.88" (276mm) H, 7.38" (187mm) W
Family:	 BRYCE

speaker Type:	IWP-8 In-wall, 2 way
Woofers:	8" Injected polypropylene
Tweeters:	1" silk soft dome, swivel
Power:	5 - 125 watts
Impedance:	8 ohms
Freq Response:	41 - 20k Hz.
Sensitivity:	90 dB
Grill Type:	Micromesh, aluminum
Finish Dims:	14.13" (359mm) H, 10.13" (257mm) W, 3" (76mm) D
Cutout Dims:	12.75" (324mm) H, 8.75" (222mm) W
Family:	 BRYCE

speaker Type:	GPW-6 In-wall, 2 way
Woofers:	6.5" white polypropylene
Tweeters:	1" silk soft dome
Power:	5 - 100 watts
Impedance:	8 ohm
Freq Response:	45 - 20kHz.
Sensitivity:	89dB (2.83 volts @ 1 meter)
EQ Adjustments:	Tweeter & woofer 0, -3, -6
Grill Type:	Ghost Style, Frameless
Finish Dims:	12.88" (326mm) H, 9.13" (233mm) W, 3.75" (97mm) D
Cutout Dims:	8" (203mm) H, 11.63" (295mm) W
Family:	 POWELL

speaker Type:	GPW-8 In-wall, 2 way
Woofers:	8" white polypropylene
Tweeters:	1" silk soft dome
Power:	5 - 125 watts
Impedance:	8 ohm
Freq Response:	40 - 20kHz.
Sensitivity:	90dB (2.83 volts @ 1 meter)
EQ Adjustments:	Tweeter & woofer 0, -3, -6
Grill Type:	Ghost Style, Frameless
Finish Dims:	14.63" (370mm) H, 10.38" (264mm) W, 3.88" (99mm) D
Cutout Dims:	9.25" (234mm) H, 13.38" (340mm) W
Family:	 POWELL